MAAA

MAAA FLIGHT PROFICIENCY SCHEME

FLIGHT REQUIREMENTS & TEST CHECK SHEET

MULTIROTOR – SILVER WINGS

This Test is to be assessed by an MAAA Instructor.

The requirements specified have been determined by the MAAA and are not to be varied.

Silver Wings (Multirotor) are awarded when a member demonstrates, in the course of one session that he/she has the skills to perform the listed manoeuvres, detailed in the diagrams provided, in a safe, confident and competent manner. GPS based functions or aids are **not** to be used at any time during the test.

competent manner. GPS based functions or aids are not to be used at any time during the test.	
This is to certify that	
of	
Club	to Club
has demonstrated the degree of proficiency in radio controlled flying of model aircraft in accordance with MOP027 to be awarded the MAAA Silver Wings (Multirotor).	
Signature MAAA Instructor's Name (BLOCK LETTERS) AUS No.	Date
At the successful completion of the test this form shall be completed by the Instructor and sent to the State Association . Note: Wings will be sent to Pilot unless Club address is noted below.	
Manoeuvres	Flight
1 Pre-flight Training (must be completed prior to flying)	
Dexterity of the pilot with his equipment	
Theoretical knowledge	
Pre-flight checks including arming/disarming electric motors, demonstration of switch functions and radio range checks	
2 Lift off to eye-level height, hover for ten seconds and land.	
2 Lift on to eye-level neight, hover for ten seconds and land.	
3 Lift off to skid eye level height, briefly hover, followed by a straight outward flight of 10 metres, briefly hover, then return 'tail' first in straight flight, briefly hover and land.	
4 Lift off to skid eye level height and stop. Model turns 90 degrees left or right, then without pausing, turns through 180 degrees ('tail' towards pilot), then without pausing turns 90 degrees back to 'tail-in' to the pilot, pauses then lands.	
E Litt att to and level briefly become their accounts a continuous action of Eurobiah and 40m wide	
5 Lift off to eye level, briefly hover, then execute a vertical rectangle, 5m high and 10m wide, returning to the point above the start point, briefly hover and land.	
6 Lift off to eye level, briefly hover, then turning fly slowly and smoothly left or right at a constant	
height a distance of 10m, then without stopping, turn away from the pilot and fly back towards the starting point continuing a further 10m on the opposite side before turning away from the pilot and returning to the point above the starting point, brief hover and land.	
Lift off and perform a 45 degree ascent directly to the side (upwind) of the central helipad to a position approximately 10m above ground. Pause, proceed 20m to the opposite side of the helipad (downwind) at a constant altitude, Pause, perform a 45 degree descent to the landing position (the central helipad) where the model hovers briefly and lands.	
Manoeuvres are to be executed with the pilot standing a minimum distance of 10 metres behind the Central Helipad, using a flight line layout with one flag or marker located 5 metres to each side of the Central Helipad. All manoeuvres are flown 'tail' toward the pilot except where specified.	
Wings to be sent to Pilot? YES / NO (If NO, note address below) Strike out as applicable	

Multirotor Silver Wings Manoeuvres

Note: The helicopter has been retained in these diagrams to indicate the orientation of the multirotor and the direction of the manoeuvre.

